1400

PE tarpaulin Extra

EXTRA 240 GR/M²

PE tarpaulins, heavyweight and durable, find applications in camping, construction, roofing, agriculture, freight transport, events, vehicle protection, and industrial settings. Versatile and weather-resistant, they offer reliable protection in diverse environments.



Technical specifications

Tensile strength	1022N / 5cm According to ISO 13937-1
Tear strength	184N / 5cm According to ISO 13937-1
UV resistance	200Kly
Temperature resistance	-40ºC / +80ºC

Product information

- Woven HDPE tape with both sides LDPE coating
- 2% UV stabilized
- All around welded hem with reinforcing PP rope and brass eyelets every meter, inner ø18mm
- Each tarpaulin packed in a crystal clear PE bag, with neutral COVER insert leaflet, 4 languages and EAN-code
- Transport packing in sturdy 5-layer water resistant carton boxes
- Delivery on Euro pallets (80×120cm)
- Pallet height; semi approx. 125cm, full approx. 250cm
- 18 months warranty on UV resistance

Customization

- Custom-size: small buying quantity, delivery time 3-4 months
- Different color and weight: minimum purchase order quantity approx. 20,000m², delivery time 3-4 months

- Private label, box or bale packing
- Product print possibility
- Optional: CORONA surface treatment technology for better adhesion of printed texts
- Optional: VCI anti-corrosion method actively protects your metal from oxidation (VpCI)

Sizes

Finished size (m)	Green	Blue	White	Quantity per box	Quantity per half pallet	Quantity per full pallet
1.5 × 6	✓			10	200	320
2 × 3	✓	✓	✓	12	288	432
3 × 4	✓	✓	✓	6	144	216
4 × 6	✓	✓	✓	3	72	132
4 × 8			✓	2	56	80
5 × 6			✓	2	56	72
5 × 15		✓		1	36	52
6 × 8	✓	✓	✓	2	40	64
6 × 10	✓	✓	✓	1	28	40
8 × 10	✓	✓	✓	1	20	32
8 × 12	✓	✓	✓	1	20	28
10 × 12	✓	✓	✓	1	16	24
10 × 15	✓	✓	✓	1	12	12
10 × 20	✓	✓	✓	1	8	8
15 × 20	✓	✓	✓	1	8	8
20 × 20	✓	✓	✓	1	4	4