2820

PE leno tarp rolled

STANDARD 180 GR/M²

Reinforced scaffold wrap is designed to reduce wind load on construction scaffolding. It provides a protective barrier against strong winds, enhancing scaffold stability and increasing safety for workers and materials. With its weather-resistant properties, it also helps prevent damage from wind, making it an essential component of construction protection in windy conditions.



Technical specifications

Tensile strength	491N / 5cm According to ISO 13937-1
Tear strength	93N / 5cm According to ISO 13937-1
Temperature resistance	-40ºC / +80ºC

Product information

- HDPE mesh with both sides transparent LDPE coating
- 2% UV stabilized
- Longitudinal welded PE eyelet bands with pre-punched eyelets holes at every 10cm interval, inner Ø 15 mm (one side double)
- Each piece packed in a crystal clear PE bag with neutral COVER sticker, 4 languages and EAN code
- Transport packing in bales of leno tarp
- Delivery on Euro pallets (80×120cm)
- Pallet height approx. 115cm

Customization

- Custom-size, different color and/or weight, minimum order quantity and term of delivery after consultation
- Private label, box or bale packing
- Also available in Flame Retardant (FR) quality
- Product print possibility
- Optional: CORONA surface treatment technology for better adhesion of printed texts

Sizes

Finished size (m)	White	Mounting strap spacing (cm)	Rolls per pallet
2.70 × 20	✓	14 + 7 + 7 + 7	90
3.20 × 20	✓	14 + 7 + 7 + 7	90